

R&S® HM8000 Modular System

Configure your individual set of test instruments



The perfect choice for

Education

Hobbyists

Maintenance & repair

Key specifications

Function generator	up to 10 MHz, up to 10 V _{pp} waveforms: sine, triangle, square wave, pulse, DC
Triple power supply	2 x 0 V to 20 V/0.5 A, 1 x 5 V/1 A
LCR meter	measurement functions: L, C, R, Θ , Q, D, Z basic accuracy: 0.2 %
4 3/4-digit multimeter	50 000 counts basic accuracy: 0.05 %

Key features

- Unsurpassed price-performance ratio and enormous flexibility of plug-in system
- Multimeter, LCR meter, function generator and triple power supply can be combined into a set
- Mainframe allows simultaneous operation of two modules
- Space-saving by stacking up to 5 mainframes
- Blank module available for customized instrument design

Your benefit

Unsurpassed price-performance ratio

Flexibility

Blank module available

Features

Very suitable for education; high performance for any type of basic electronic training

Four different instruments can be combined into a space-saving set to meet individual requirements

- To easily build customized circuitries
- Power is supplied by the mainframe
- Can also be used to fill unused slots

► For more information, visit
www.rohde-schwarz.com/product/HM8001

R&S®HM8030-6 function generator



- Frequency range: 50 mHz to 10 MHz
- Output voltage: up to 10 Vpp (into 50Ω)
- Waveforms: sine, triangle, square wave, pulse, DC
- Distortion: < 0.5 % up to 1 MHz, rise and fall time of typ. 15 ns

R&S®HM8040-3 triple power supply



- 2 x 0 V to 20 V/0.5 A; 1 x 5 V/1 A
- 3-digit switchable displays for current and voltage
- Display resolution: 0.1 V/1 mA
- Adjustable current limiting and electronic fuse

R&S®HM8018 LCR meter



- Measurement functions: L, C, R, Θ , Q/D, |Z|
- Basic accuracy: 0.2 %
- Meas. frequencies: 100 Hz, 120 Hz, 1 kHz, 10 kHz, 25 kHz
- Max. resolution: 0.001 Ω , 0.001 pF, 0.01 μ H

R&S®HM8012 4 $\frac{3}{4}$ -digit multimeter



- 4 $\frac{3}{4}$ -digit display with 50 000 counts
- Basic accuracy: 0.05 %
- Max. resolution: 10 μ V, 0.01 dBm, 10 nA, 10 m Ω , 0.1 $^{\circ}$ C
- Offset function and relative value measurements

R&S®HM8001 mainframe



- **Module supply voltages:**
2 x 8 V (AC), max. 5.5 A each
2 x 5 V (DC), max. 1 A each
4 x 20 V (DC), max. 0.5 A each
- Power consumption per module: max. 25 W
- DC voltages electronically regulated, floating and short-circuit proof

Ordering information

Step 1: choose mainframe (fits up to 2 modules)

R&S®HM8001-2	Mainframe

Step 2: choose instrument modules

R&S®HM8030-6	Function generator
R&S®HM8040-3	Triple power supply
R&S®HM8012	4 $\frac{3}{4}$ -digit multimeter
R&S®HM8018	LCR meter
R&S®HM800	Blank module



R&S®HM800 blank module

Rohde & Schwarz GmbH & Co. KG

Europe, Africa, Middle East | +49 89 4129 12345
 North America | 1 888 TEST RSA (1 888 837 87 72)
 Latin America | +1 410 910 79 88
 Asia Pacific | +65 65 13 04 88
 China | +86 800 810 82 28 | +86 400 650 58 96
www.rohde-schwarz.com
customersupport@rohde-schwarz.com

R&S® is a registered trademark of Rohde & Schwarz GmbH & Co. KG
 PD 5215.3527.32 | Version 01.00 | July 2017 (ks)
 Trade names are trademarks of the owners
 R&S®HM8000 Modular System
 Data without tolerance limits is not binding | Subject to change
 © 2017 Rohde & Schwarz GmbH & Co. KG | 81671 Munich, Germany

Thurlby Thandar Instrument Distribution
 Glebe Road, Huntingdon, PE29 7DR, UK
+44 (0)1480 412 451
sales@ttid.co.uk
www.ttid.co.uk

TTid.co.uk
THURLBY THANDAR
 instrument distribution