



FACTORY CERTIFIED. PERFORMANCE READY.

Full List

Thurlby Thandar Instrument Distribution
Glebe Road, Huntingdon, PE29 7DR, UK
+44 (0)1480 412 451
sales@ttid.co.uk
www.ttid.co.uk

T T id.co.uk
THURLBY THANDAR
instrument distribution

Discounts apply to the products listed below only.

All products are being sold on a first-come first-served basis. Available while stocks last!

Model Number	Description	ENCORE Discount
1754	SAFETY UNIVERSAL TEST LEAD KIT	15%
2015	THD DIGITAL MULTIMETER	15%
2016	THD DIGITAL MULTIMETER	15%
2430	IKW PULSE SOURCEMETER	15%
2440	5A SOURCEMETER	15%
2450	Interactive Digital SourceMeter	15%
2460	Hi Current Digital SourceMeter	15%
2510	TEC SOURCE METER	15%
3390	50MHz ARBITRARY WAVEFORM GENERATOR	15%
3730	6 X 16 HIGH DENSITY MATRIX CARD	15%
3731	6X16 HIGH SPEED REED RELAY MATRIX CARD	15%
3732	QUAD 4X28 REED RELAY MATRIX CARD	15%
3740	28 INDEPENDENT FORM C AND 4 HIGH CURENT FORM A CARD	15%
3750	MULTIFUNCTION CARD 40 DIO,4 COUNTERS, 2AO	15%
5804	4 TERMINAL TEST LEAD SET	15%
5806	KELVIN CLIP LEADS	15%
7002	10-SLOT SWITCH MAINFRAME	15%
7035	9-BANK, 1X4 MULTIPLEXER CARD	15%
7036	40 CHAN SINGLE POLE RELAY CARD	15%
7072	8X12 SEMICONDUCTOR MATRIX CARD	15%
7152	LOW CURRENT MATRIX CARD	15%
7153	HI VOLT LOW CURRENT CARD	15%
7154	2-POLE HIGH VOLTAGE CARD	15%
7158	LOW CURRENT SCANNER CARD	15%
7700	20 CHANNEL MULTIPLEXER	15%
7701	32 CHANNEL DIFFERENTIAL MULTIPLEXER WITH	50%
7703	32 CHANNEL HI SPEED DIFF MUX	15%
7705	40 CHANNEL CONTROL MODULE	15%
7707	MULTIPLEXER DIGITAL I/O MODULE WITH 25 P	15%
7711	2GHZ, DUAL 1X4, 50 OHM MULTIPLEXER CARD	15%
7712	3.5GHZ, DUAL 1X4, 50 OHM MULTIPLEXER CAR	15%
8010	TEST FIXTURE FOR 265xA	15%
8020	HIGH POWER INTERFACE PANEL	15%
1741C	Analog Composite PAL / NTSC Dual Standards Waveform / Vector / SCH Monitor-4 Inputs with	20%
2000/E	6.5 DIGIT MULTIMETER AT 220V	15%
2000/E/2000-SCAN	6.5 DMM WITH SCAN OPTION @ 220V	35%
2000-SCAN	SCANNER BOARD	15%
2010/E	LOW NOISE 7.5 DIGIT DMM @220V	15%

2015/E	THD 6.5 DIGIT DMM @ 220V	15%
2016-P	AUDIO ANALYZING DMM W/9V SRC	15%
2100/120	6 1/2 DIGIT DMM SET TO 120V	15%
2100/220	6 1/2 DIGIT DMM SET TO 220V	15%
2100/230-240	6 1/2 DIGIT DMM SET TO 230-240V	15%
2107-17	LO THERMAL INPUT CABLE w SPADE LUGS (5M)	15%
2107-4	LOW THERMAL INPUT CABLE	15%
2110-120	5.5 DIGIT DMM (USB ONLY) 120V VERSION	15%
2110-120-GPIB	5.5 DIGIT DMM WITH GPIB 120V VERSION	15%
2110-220	5.5 DIGIT DMM (USB ONLY) 220V VERSION	15%
2110-220-GPIB	5.5 DIGIT DMM WITH GPIB 220V VERSION	15%
2110-240	5.5 DIGIT DMM (USB ONLY) 240V VERSION	15%
2110-240-GPIB	5.5 DIGIT DMM WITH GPIB 240V VERSION	15%
2200-32-3	Power Supply, 32 Volts, 3 Amps DC Programmable	15%
2200-72-1	Power Supply, 72 Volts, 1.2 Amps DC Programmable	15%
2220-30-1	PROGRAMMABLE DUAL CHANNEL DC POWER SUPPLY	15%
2220G-30-1	PROGRAMMABLE DUAL CHANNEL DC POWER SUPPLY	15%
2220GJ-30-1	Programmable Dual Channel DC Power Supply for Japan	n/a
2220J-30-1	Programmable Dual Channel DC Power Supply for Japan	n/a
2230-30-1	PROGRAMMABLE TRIPLE CHANNEL DC POWER SUPPLY	15%
2260-007	Cable for 3 units in Parallel connection	10%
2260B-250-13	Programmable DC Power Supply, 250V, 13.5A, 1080W	15%
2260B-250-4	Programmable DC Power Supply, 250V, 4.5A, 360W	10%
2260B-250-9	Programmable DC Power Supply, 250V, 9A, 720W	10%
2260B-30-108	Programmable DC Power Supply, 30V, 108A, 1080W	15%
2260B-30-36	Programmable DC Power Supply, 30V, 36A, 360W	15%
2260B-800-4	Programmable DC Power Supply, 800V, 4.32A, 1080W	15%
2260B-80-13	Programmable DC Power Supply, 80V, 13.5A, 360W	15%
2260B-80-27	Programmable DC Power Supply, 80V, 27A, 720W	15%
2268-100-8	850W DC Power Supply, 100V, 8.5A	30%
2268-150-5	850W DC Power Supply, 150V, 5.6A	30%
2268-20-42	850W DC Power Supply, 20V, 42A	30%
2268-40-21	850W DC Power Supply, 40V, 21A	30%
2268-60-14	850W DC Power Supply, 60V, 14A	30%
2268-80-10	850W DC Power Supply, 80V, 10.5A	30%
2268-RMK-1	RACK MOUNT KIT FOR ONE SERIES 2268 DC POWER SUPPLY	15%
2280S-60-3	Programmable Single Channel DC Power Supply, 60V, 3.2A, 192W	15%
2281S-20-6	Precision DC supply and battery simulator, 20V, 6A, 120W	15%
2290-10	10KV POWER SUPPLY	15%
2290J-5	5KV POWER SUPPLY, 100VAC NOMINAL INPUT VOLTAGE	15%
2290-PM-200	10KV PROTECTION MODULE	15%
2306-PJ	DUAL CHAN BATTERY CHARGER SIM. W/500MA R	15%
2306-VS	POWER SUPPLY WITH READOUT/TRIGGER	15%
2380-120-60	Programmable DC Electronic Load, 120V, 60A, 250W	15%
2380-500-15	Programmable DC Electronic Load, 500V, 15A, 200W	15%
2380-500-30	Programmable DC Electronic Load, 500V, 30A, 750W	15%
2380J-500-30	Programmable DC Electronic Load, 500V, 30A, 750W-Japan only	15%
2400-C	SOURCEMETER	15%
2410-C	SOURCE METER	15%
2420-C	SOURCEMETER	15%

2430-C	SOURCEMETER	15%
2510-AT	AUTOTUNING TEC SOURCE METER	15%
2600-ALG-2	LOW NOISE TRIAX CABLE WITH ALLIGATOR CLIPS	10%
2600-PCT-2B	HIGH CURRENT PARAMETRIC CURVE TRACER	10%
2601B	SYSTEM SOURCEMETER SINGLE CHANNEL, 40V	15%
2604B	SOURCEMETER - DUAL CHANNEL, 40V	35%
2611B	SYSTEM SOURCEMETER - SINGLE CHANNEL, 200V	20%
2611B-L	SourceMeter SMU Instrument,1 channel, No Display (1pA,200V,1.5A DC/10A Pulse)	n/a
2612B	SYSTEM SOURCEMETER - DUAL CHANNEL, 200V	15%
2614B	SOURCEMETER - DUAL CHANNEL, 200V	15%
2635B	SYSTEM SOURCEMETER -SINGLE CHANNEL, 200V, LOW CURRENT	15%
2636B	SYSTEM SOURCEMETER - DUAL CHANNEL, 200V, LOW CURRENT	15%
2651A	HIGH CURRENT SMU - SINGLE CHANNEL	15%
2657A	HIGH VOLTAGE SMU - SINGLE CHANNEL	15%
2657A-LIM-3	LOW INTERCONNECT MODULE	60%
2701/E	DMM/DATA ACQUISITION SYSTEM @ 220V	15%
3706A	6 SLOT SYSTEM SWITCH WITH HIGH PERFORMANCE DMM	15%
3706A-SNFP	3706A-S WITHOUT FRONT PANEL DISPLAY AND KEYPAD	15%
3721-MTC-3	50 PIN FEMALE TO MALE D-SUB CABLE ASSY, 3M	15%
3721-ST	SCREW TERMINAL PANEL WITH CJC SENSOR FOR 3721 CARD	15%
3722-MTC-3	104 PIN MALE TO FEMALE D-SUB CABLE ASSY, 3M	15%
3723-ST	SCREW TERMINAL PANEL FOR 3723 CARD	15%
3723-ST-1	SCREW TERMINAL PANEL FOR 3723 CARD (SINGLE POLE)	15%
3724-ST	SCREW TERMINAL PANEL WITH CJC SENSOR FOR 3724 CARD	15%
3732-ST-C	SCREW TERM FOR 3732 CARD, COL. EXPANSION	15%
3732-ST-R	SCREW TERM FOR 3732 CARD, ROW EXPANSION	15%
3791-KIT78-R	78 PIN FEMALE D-SUB CONN KIT (SOLDER CUP CONTACTS)	15%
4200A-CVIV	I-V/C-V MULTI-SWITCH MODULE	10%
4200A-SCS	PARAMETER ANALYZER MAINFRAME	10%
4200-PA	REMOTE PREAMPLIFIER MODULE	15%
4200-PMU-PROBER	4225-PMU/4220-PGU SMU/INTERCONNECTION KIT	15%
4200-SMU	MEDIUM POWER SOURCE-MEASURE UNIT	15%
4210-CVU	CAPACITANCE-VOLTAGE UNIT	15%
4210-SMU	HIGH POWER SOURCE-MEASURE UNIT	15%
4225-PMU	ULTRA-FAST PULSE MEASURE UNIT	15%
4225-RPM	REMOTE PREAMPLIFIER/SWITCH MODULE	15%
4288-1	SINGLE FIXED RACK MOUNTING KIT	15%
4288-2	DUAL FIXED RACK MOUNTING KIT	15%
4288-4	SIDE-BY-SIDE RACK MOUNT KIT	15%
4288-7	FIXED REAR RACK MOUNT KIT	10%
4299-1	HEAVY DUTY RACK MOUNT KIT 2600 SERIES SINGLE UNIT	10%
4299-2	HEAVY DUTY RACK MOUNT KIT FOR TWO UNITS	15%
7002-HD-MTX1	6X32 MATRIX CARD	15%
7002-HD-MUX1	QUAD 1X40 MULTIPLEXING CARD	15%
7007-1	SHIELDED GPIB CABLE,1M (3.2FT)	15%
7011-S	QUAD 1X10 MULTIPLEXER CARD	15%
7012-S	4X10 MATRIX CARD	15%
7013-C	20 CHANNEL RELAY SWITCH CARD	15%
7015-C	40 CHAN SOLID ST MULTIPLEXER	15%
7018-S	28 CHANNEL 3 POLE CARD	15%

7020-D	DIGITAL I/O CARD	15%
7078-TRX-BNC	3-SLOT MALE TRIAX TO BNC ADAPTER	15%
707B	6 SLOT SEMICONDUCTOR SWITCHING MAINFRAME	15%
708B	1 SLOT SEMICONDUCTOR SWITCHING MAINFRAME	15%
7111-S	40 CHANNEL FORM C SWITCH CARD	15%
7173-50	2-POLE HI-FREQ MATRIX CARD	15%
80A02	EOS/ESD PROTECTION MODULE FOR ELECTRICAL STATIC ISOLATION OF TEKTRONIX ELECTRICAL	40%
80A03	TEKCONNECT PROBE INTERFACE MODULE	40%
80A06	Pattern Sync TRIGGER MODULE	60%
80C07B	OPTICAL SAMPLING MODULE; 2.488 GB/S OC48/STM16,2.500 GB/S 2GBE,2.500 GB/S INFINIBAND	40%
80C08D	Single channel optical sampling module; 10G Optical Reference Receiver Filters; 12 GHz optical	40%
80C10C	Single Channel, 65/80 GHz Optical Sampling Module(must specify one of options F1, F2, or F3)	40%
80C14	14+ GHz, Broad WaveLength, Amplified Optical Sampling Module	40%
80E04	SAMPLING MODULE; DUAL,20 GHZ W/TDR ELECTRICAL SAMPLING MODULE - CERTIFICATE OF	40%
80E10B	8000 Series, Dual Channel, 50 GHz, Remote Electrical Sampling Module w/ TDR (includes D1)	n/a
80E11X1	8000 Series, Single Channel, 70 GHz, Ultra-low Jitter, Electrical Sampling Module (includes D1)	40%
AC280-FL	Suregrip Hook Clips, Set, SAFETY CONTROLLED	20%
AC3000	Soft Carrying Case	15%
ACD3000	Soft carrying case for MDO3000 Series oscilloscopes	20%
ACD4000B	Soft Carrying Case	15%
AFG3021B	ARBITRARY/FUNCTION GENERATOR, 25 MHZ, 1 CHANNEL, GPIB and LAN	30%
AFG3151C	Arbitrary Function Generator: 1Channel, 150MHz Bandwidth, 1GSa/s sampling rate, 128k point	20%
AFG3152C	Arbitrary Function Generator: 2Channel, 150MHz Bandwidth, 1GSa/s sampling rate, 128k point	20%
AFG3251C	Arbitrary Function Generator: 1Channel, 240MHz Bandwidth, 2GSa/s sampling rate, 128k point	35%
AGL7	Analog Genlock Module for TG8000 or TG700 mainframe - 3 black outputs, 1 genlock loopthro	50%
AMM768	AMM768 AUDIO MULTI-CHANNEL MONITOR BASE UNIT (MUST ORDER AN AUDIO OPTION). CE	80%
AVG7	Component and Composite Analog Test Signal Generator Module for TG8000 or TG700 mainfra	80%
AWG4162	Arbitrary Waveform Generator, 2 analog Channels, 2.5 GS/s sampling rate, 14-bit resolution, 1	35%
AWG70001A	Arbitrary Waveform Generator: 1-channel, 2G samples record length, 10 bit	15%
AWG70002A	Arbitrary Waveform Generator: 2-channel, 2G samples record length, 10 bit	15%
AWVG7	Analog Wideband Test Signal Generator Module for TG8000 or TG700 mainframe - 2 identical c	80%
BA1600	1.6 Gb/s Pattern Generator and Error Analyzer	15%
BG7	Analog Black Generator Module for TG8000 or TG700 mainframe - 4 independently selectable	50%
BSA12500ISI	Differential ISI Board	15%
BSA125C	BERTScope 12.5 Gb/s Pattern Generator and Error Analyzer	25%
BSA286C	BSA BERT with Generation performance to 28.6Gbps and full rate error detection to 26Gbps. E	60%
BSA286CL	BSA286CL BERTScope Low Noise 28.6 Gb/s Bit Error Ratio Analyzer	40%
BSASATATEE	BSA-SATA-Tee for OOB Signaling	60%
CL200	Current Clamp, 0.5A - 200A	15%
CR125A	12.5 Gb/s Clock Recovery Instrument	15%
CR286A	28.6 Gb/s Clock Recovery Instrument	15%
CT-1000-M	Fixed-Core Current Transducer, Hall Effect, up to 1000A	15%
CT2	CURRENT XMFR; 200MHZ 36A W/PROBE - STATEMENT OF COMPLIANCE WITH THIS PRODUCT	15%
DF-A0047-C1	Includes DF-A0047 antenna and DF-A0047-01 extension	15%
DMM4020	Digital Multimeter, 5.5 digits 0.015% accuracy, dual display	15%
DMM4040	Digital Precision Multimeter, 6.5 digits 0.0035% accuracy, dual/graphic display	15%
DMM4050	Digital Precision Multimeter, 6.5 digits 0.0024% accuracy, dual/graphic display	15%
DPO2002B	Oscilloscope; Digital Phosphor, 70 MHz, 1 GS/s, 1M record length, 2-ch, Color Display, 5-year V	25%
DPO2004B	Oscilloscope; Digital Phosphor, 70 MHz, 1 GS/s, 1M record length, 4-ch, Color Display, 5-year V	20%
DPO2BND	Application Module; Bundle module, including DPO2AUTO, DPO2COMP & DPO2EMBD, for MS	20%

DPO2EMBD	Application Module: Embedded Serial Triggering and Analysis (I2C, SPI)	20%
DPO3AUDIO	Application Module: Audio Serial Triggering and Analysis (I2S, LJ, RJ, TDM)	15%
DPO3COMP	Application Module: Computer Serial Triggering and Analysis (RS-232/422/485/UART)	15%
DPO3EMBD	Application Module: Embedded Serial Triggering and Analysis (I2C, SPI)	15%
DPO4BND	Application Module; Bundle module for MDO/MSO/DPO4000B and MDO4000 Series (Includes	15%
DPO70604C	6 GHz Digital Phosphor Oscilloscope; 4 analog channels	15%
DPO70804C	8 GHz Digital Phosphor Oscilloscope; 4 analog channels	15%
DPO72304DX	23 GHz Digital Phosphor Oscilloscope; 4 analog channels	15%
DPO72504DX	25 GHz Digital Phosphor Oscilloscope; 4 analog channels	15%
DPO73304DX	33 GHz Digital Phosphor Oscilloscope; 4 analog channels	15%
DPO73304SX	33 GHz Digital Phosphor Oscilloscope; 2 Ch, 33GHz, 100GS/s or 4 Ch, 23GHz, 50GS/s	15%
DPO77002SX	70 GHz ATI Performance Oscilloscope; 1 Ch, 70GHz, 200GS/s or 2 Ch, 33GHz, 100GS/s	15%
DPP125C	1-12.5 Gb/s 3 Tap Digital Pre-Emphasis Processor	25%
DVG7	SD-SDI Test Signal Generator Module for TG8000 or TG700 mainframe - 2 identical SD-SDI test	80%
ECO422D	CHANGEOVER UNIT; STANDARD DEFINITION/HIGH DEFINITION-STATEMENT OF COMPLIANCE I	60%
ECO8000	ECO (automatic changeover) base unit - 3 x BNC channels (black burst, HD tri-level sync, AES/D	60%
ECO8020	ECO (automatic changeover) base unit - 5 x high-density BNC channels (black burst, HD tri-leve	60%
FCA3003	Timer/Counter/Analyzer, 300MHz/3GHz, 100 ps, Std Timebase	15%
FCA3103	Timer/Counter/Analyzer, 300MHz/3GHz, 50 ps, Std Timebase	60%
FZ-G1-N	Controller for USB Spectrum Analyzers, Panasonic ToughPad FZ-G1. Includes tablet, battery, dig	15%
GPS7	GPS Master Clock Synchronization and Timecode Module for TG8000 or TG700 mainframe - int	80%
H500	6.2 GHz Spectrum Analyzer for Signal Analysis, Certificate of Traceable Calibration Standard	70%
HD3G7	3G/HD-SDI Test Signal Generator Module for TG8000 or TG700 mainframe - 2 identical 3G/HD-	20%
HDVG7	HD-SDI Test Signal Generator Module for TG8000 or TG700 mainframe - 2 identical HD-SDI test	80%
HV-CA-554-1	HV TRIAX CABLE, 1 M, MALE TO MALE	15%
KPCI-488LPA	LOW PROFILE IEEE-488 INTERFACE BOARD	15%
LE160	16Gbps Linear Equalizer	25%
LE320	32Gbps Linear Equalizer	25%
MCA3027	Microwave/Counter Analyzer & Power Meter, 300MHz/27GHz, Med Timebase	60%
MDO3012	Mixed Domain Oscilloscope; (2) 100MHz analog channels, 10M record length, 100MHz spectru	15%
MDO3102	Mixed Domain Oscilloscope; (2) 1GHz analog channels, 10M record length, 1GHz spectrum ana	15%
MDO3104	Mixed Domain Oscilloscope; (4) 1GHz analog channels, 10M record length, 1GHz spectrum ana	15%
MDO3BND	Application Module; Bundle module for MDO3000 Series (Includes MDO3AERO,MDO3AUDIO, I	15%
MDO3EMBD	Application Module; Embedded serial triggering and analysis (I2C, SPI)	15%
MDO3LMT	Application Module; Limit/Mask test	15%
MDO3SA	Increase spectrum analyzer input frequency to 3GHz on MDO3000 Series oscilloscope	15%
MDO4024C	Mixed Domain Oscilloscope; (4) 200 MHz analog channels, 20M record length, 3-year warranty	15%
MDO4034C	Mixed Domain Oscilloscope; (4) 350 MHz analog channels, 20M record length, 3-year warranty	15%
MDO4104C	Mixed Domain Oscilloscope; (4) 1 GHz analog channels, 20M record length, 3-year warranty, C	15%
MDO4TRIG	Advanced RF Triggering Application Module - Width, Runt, Timeout, and Logic triggers on the R	35%
MPI-RACK-MM	19INCH, 3RU DUAL RACK CABINET, USB/HEADPHONE CONNECTOR FOR ONE MPI UNIT or TWO	10%
MSO2004B	Mixed Signal Oscilloscope; Digital Phosphor, 70 MHz, 1 GS/s, 1M record length, 4+16-ch, Color	20%
MSO2014	Mixed Signal Oscilloscope; Digital Phosphor, 100 MHz, 1 GS/s, 1M record length, 4+16-ch, Colo	25%
MSO4034B	Mixed Signal Oscilloscope; Digital Phosphor, 350MHz, 2.5GS/s, 20M Record Length, 4+16 ch, C	25%
MSO5204B	Mixed Signal Oscilloscope; Digital Phosphor, 2GHz, 10/5GS/s (2/4 channels), 25M Record Leng	15%
MSO70404C	4 GHz Mixed Signal Oscilloscope; 4 analog / 16 logic channels	15%
MSO70604C	6 GHz Mixed Signal Oscilloscope; 4 analog / 16 logic channels	15%
MSO70804C	8 GHz Mixed Signal Oscilloscope; 4 analog / 16 logic channels	15%
MSO72304DX	23 GHz Mixed Signal Oscilloscope; 4 analog / 16 logic channels	15%
MTS4000	MPEG TEST SYSTEM INCORPORATING DESKTOP PLATFORM. THIS INCLUDES: REAL AND DEFER	30%

NEX-DDR3MCI96SC	Nexus Technology, DDR3 MCI x16 scope direct attach component interposer, data narrow	15%
NEX-DDR3MP78BS	NEXUS TECHNOLOGY,DDR3 x4/x8 Socket Chip Interposer for Oscilloscope Probes	15%
NEX-DDR3MP96BS	NEXUS TECHNOLOGY, INC DDR3 x16 Solder Chip Interposer for Oscilloscope Probes	15%
NEX-MCA4-DDR3	MCA4000 Memory Compliance Analyzer with support for DDR3 2133MT/s	15%
NEX-MCA5-LP4-QT	Nexus Technology Qualcomm Custom MCA 5000 Memory Compliance Analyzer configured for L	35%
NEX-PRB1XL	NEXUS TECHNOLOGY, INC. DISTRIBUTED (PASSIVE) 1X PROBE, TLA TO HCD, LONG HCD PROBE,	15%
NEX-PRB-P69PSV	Nexus Technology PRB6960 Passive Probe for use with Nexus Memory Compliane Analyzer	15%
NEX-SODDR3INTR7	DDR3 SO-DIMM interposer with ECC	15%
NEX-SODDR3INTR-	Nexus Technology, DDR3 SODIMM Interposer with A,C,C on one HCD Connector	15%
P5050B	PASSIVE PROBE; 10X 500 MHZ PASSIVE VOLTAGE PROBE; COVERED BNC	15%
P5122	High Voltage Probe: 200 MHz, 100X, 1 kVRMS CAT II, Single-ended, BNC	15%
P5150	High Voltage PROBE; 50X, 500 MHZ, 2.5 kV	15%
P5910	17-Channel General Purpose Probe for TLA6400 Logic Analyzers; Fits both 0.100 in. and 2 mm s	15%
P5934	34-Channel Mictor Probe for TLA6400 Logic Analyzers; Single-Ended Data,Single-Ended Clock	15%
P6139B	Passive Probe: 500 MHz, 10X, BNC	15%
P6243	Active Probe: 1 GHz, 10X, Single-ended, TekProbe	15%
P6245	PROBE,FET ACT; >1.5GHZ,10X,<1PF,TDS SERIES - CERTIFICATE OF TRACEABLE CALIBRATION STA	15%
P6246	Differential Probe: 400 MHz, 1X/10X, +/- 8.5V, TekProbe	15%
P6247	PROBE,DIFF,ACT; 1GHZ BW,+/- 0.85/8.5V,1PF,TPI - CERTIFICATE OF TRACEABLE CALIBRATION S	15%
P6248	PROBE; 1.7GHZ DIFFERENTIAL - CERTIFICATE OF TRACEABLE CALIBRATION STANDARD	15%
P6251	PROBE, DIFF HV, WITH TEKPROBE-BNC INTERFACE, 42V, 1GHZ - CERTIFICATE OF TRACEABLE CA	15%
P6316	MSO PROBE; 16 CHANNEL GENERAL PURPOSE PROBE	20%
P6330	PROBE; DIFFERENTIAL; 3.5 GHZ BW, BNC, +/-1.75 V DIFFERENTIAL DYNAMIC RANGE, +5V -4V C	15%
P6410	GENERAL-PURPOSE PROBE AND ACCESSORIES, 17 CHANNEL, FOR TLA5000 SERIES LOGIC ANAL	30%
P6516	MSO PROBE; 16 CH GENERAL PURPOSE PROBE FOR THE MSO4000 SERIES.	15%
P6616	MSO Probe; 16 Channel general purpose logic probe for the MSO5000 and MSO4000B Series.	15%
P6703B	O/E CONVERTER; DC-1GHZ, 1100-1650NM, TPI - CERTIFICATE OF TRACEABLE CALIBRATION STA	15%
P6717A	PROBE, GENERAL PURPOSE UPGRADED W/ ACCESSORY KIT	15%
P6750	PROBE, P6750 DMAX FOR MSO70K INSTRUMENTS	15%
P6780	17 channel differential input logic probe for MSO70000 with solder-in accessories	15%
P67SA01SD	PCIE3 Serial,1 Differential Input,Solder Down Probe	15%
P67SA08S	PCIE3 Serial,16 Differential Inputs,x8,Slot Interposer Probe	15%
P67SA16	PCIE3 Serial,16 Differential Inputs,x8,Midbus Probe	15%
P67SA16G2	PCIE SERIAL, 16 DIFFERENTIAL INPUTS, X8, MIDBUS PROBE FOR TLA7SAXX MODULES TO CONN	15%
P67SA16S	PCIE3 Serial,32 Differential Inputs,x16,Slot Interposer Probe	15%
P6864	LA PROBE; LOGIC ANALYZER PROBE FOR TLA7AXX, 17 CHANNEL, HIGH DENSITY COMPRESSION	60%
P6880	PROBE,LA; LOGIC ANALYZER PROBE FOR TLA7AXX,34 CHANNEL,HIGH DENSITY COMPRESSION,S	60%
P6980	34-Channel D-Max Probe for TLA7000 Logic Analyzers; Single-Ended/Differential Data & Clock	15%
P6982	17-Channel D-Max Probe for TLA7000 Logic Analyzers; Optimized for 2x Demux; Single-Ended/	15%
P7240	PROBE, ACTIVE; 4 GHZ BW, 2.0V DYNAMIC RANGE, CERTIFICATE OF TRACEABLE CALIBRATION S	15%
P7313SMA	13 GHZ DIFFERENTIAL SIGNAL ACQUISITION SYSTEM WITH SMA INPUTS	15%
P7330	PROBE; DIFFERENTIAL; 3.5 GHz BW, +/-1.75 V DIFFERENTIAL DYNAMIC RANGE, +5V -4V COMM	15%
P7380SMA	8 GHZ DIFFERENTIAL SIGNAL ACQUISITION SYSTEM WITH SMA INPUTS,CERTIFICATE OF TRACEA	60%
P7506	6GHz TRIMODE DIFFERENTIAL PROBE	15%
P7508	8GHz TRIMODE DIFFERENTIAL PROBE	15%
P7513A	13GHz TRIMODE DIFFERENTIAL PROBE	15%
P7516	TRIMODE DIFFERENTIAL PROBE. CERTIFICATE OF TRACEABLE CALIBRATION STANDARD WITH P	15%
P7520A	TriMode Differential Probe	15%
P75PDPM	P7500 PRECISION DIFFERENTIAL PROBING MODULE	15%
P7633	33 GHz LOW NOISE TRIMODE PROBE IN CASE WITH ACCESSORIES	15%

P76CA-292	P76CA-292 PROBE TIP ASSEMBLY IN CASE WITH ACCESSORIES	15%
P76CA-292C	P76CA-292C PROBETIP ASSEMBLY IN CASE WITH ACCESSORIES	15%
P76CA-SMP	P76CA-SMP PROBE TIP ASSEMBLY IN CASE WITH ACCESSORIES	15%
P76TA	P76TA PROBE TIP ASSEMBLY IN CASE WITH ACCESSORIES	15%
P7720	20 GHz TriMode Probe with TekFlex connector technology, TekConnect interface	15%
P77BRWSR	Browser Accessory with TekFlex connector technology, 16 GHz, Range: 6Vpp per side	15%
P77DESKEW	Deskew fixture for P7700 series probes (USB power cable included)	15%
P80318	Probe kit,18GHz 100 Ohm Differential Hand Probe	15%
PA1000	PA1000 Single-Phase Power Analyzer	15%
PA3000	PA3000 Power Analyzer, 1 to 3 power phases	15%
PA4000	PA4000 Multi-phase Power Analyzer	70%
PED3202	32Gb/s Programmable Error Detector, 2-channel	50%
PED4002	40 Gb/s Programmable error detector, 2-channel	50%
PPG1251	12.5Gb/s Programmable Pattern Generator, 1-channel	50%
PPG3004	30Gb/s Programmable Pattern Generator, 4-channel	50%
PPG3204	32Gb/s Programmable Pattern Generator, 4-channel	50%
PQA600B	Picture quality analyzer platform	60%
PSM3110	USB Power Meter True Average 10MHz 8GHz, 3.5mm Male	60%
PSM3120	USB Power Meter True Average 10MHz 8GHz, N-Type Male	60%
PSM3310	USB Power Meter True Average 10MHz 18GHz, 3.5mm Male	60%
PSM3320	USB Power Meter True Average 10MHz 18GHz, N-Type Male	60%
PSM3510	USB Power Meter True Average 10MHz 26.5GHz, 3.5mm Male	60%
PSM4120	USB Power Meter Avg/Peak/Pulse 10MHz 8GHz, N-Type Male	60%
PSM4320	USB Power Meter Avg/Peak/Pulse 50MHz 18GHz, N-Type Male	60%
PSM4410	USB Power Meter Avg/Peak/Pulse 50MHz 20GHz, 3.5mm Male	60%
PSM5110	USB Power Meter Avg/Peak/Pulse +Profiling 100MHz 8GHz, 3.5mm Male	60%
PSM5120	USB Power Meter Avg/Peak/Pulse +Profiling 100MHz 8GHz, N-Type Male	60%
PSM5320	USB Power Meter Avg/Peak/Pulse +Profiling 50MHz 18GHz, N-Type Male	60%
PSM5410	USB Power Meter Avg/Peak/Pulse +Profiling 50MHz 20GHz, 3.5mm Male	60%
PSPL5310R	PHASE-MATCHED BALUN	15%
PSPL5315	DIFF PULSE SPLITTER-BALUN, SMA J-J-J	15%
PSPL5320B	DIFF PULSE SPLITTER-BALUN, SMA J-J-J	15%
PSPL5333	POWER DIVIDER, 6dB	15%
PSPL5334	QUAD DIVIDER, 12dB	15%
PSPL5350	POWER DIVIDER, 6dB	15%
PSPL5361	PICKOFF TEE, 14dB (5X)	35%
PSPL5500A	DC BLOCK, 50V	10%
PSPL5501A	DC BLOCK, 50V	15%
PSPL5508	DC BLOCK, 16V	15%
PSPL5509	DC BLOCK	15%
PSPL5530B	BIAS TEE, 12.5GHz, 200V	15%
PSPL5541A	BIAS TEE, 26GHz, 50V	15%
PSPL5542	BIAS TEE, 50GHz, 16V	15%
PSPL5543	BIAS TEE, 100V, 500mA	15%
PSPL5544	BIAS TEE, 100V, 2A	15%
PSPL5866	AMPLIFIER, 25dB GAIN, 2.5kHz-10GHz	15%
PSPL5882	AMPLIFIER, 40-45GHz, 16dB GAIN	15%
PSPL5915	LOW PASS FILTER	15%
PSPL5935	LOW PASS FILTER	15%
PWS2185	Power Supply,0-18 V, 5 Amp DC	15%

PWS2326	Power Supply, 0-32 V, 6 Amp DC	15%
PWS2721	Power Supply, 0-72 V, 1.5 Amp DC	15%
PWS4205	Power Supply, 20 Volts, 5 Amps DC Programmable	15%
PWS4602	Power Supply, 60 Volts, 2.5 Amps DC Programmable	15%
PWS4721	Power Supply, 72 Volts, 1.2 Amps DC Programmable	15%
RM3000	RACKMOUNT KIT; FOR TDS3000 FAMILY	15%
RM4000	RACK MOUNT KIT FOR DPO4000 AND MSO4000 SERIES	15%
RSA306RACK	Rackmount and stackable benchmount, RSA306 real time spectrum analyzer, holds two units	50%
RSA503A	Portable Real time USB signal analyzer, 9 kHz-3.0 GHz	15%
RSA507A	Portable Real time USB signal analyzer, 9 kHz-7.5 GHz	15%
RSA5103B	Real Time Signal Analyzer 1 Hz-3 GHz	30%
RSA5106A	Real Time Signal Analyzer 1 Hz-6.2 GHz 25 MHz Acquisition BW	70%
RSA5106B	Real Time Signal Analyzer 1 Hz-6.2 GHz	30%
RSA5126B	Real Time Signal Analyzer 1 Hz-26.5 GHz	30%
RSA603A	Real time USB signal analyzer, 9 kHz - 3.0 GHZ	15%
RSA607A	Real time USB signal analyzer, 9 kHz - 7.5 GHZ	15%
RSA6120B	REAL TIME SIGNAL ANALYZER; 9 kHz-20 GHz, 40 MHz Acq. BW	30%
S46-18	18 GHZ UNTERMINATED RF SWITCH SYSTEM	15%
S46T-BBBB0000000	S46 W/4 SP6T TERM 26.5GHZ	15%
SA2500	6.2 GHz Spectrum Analyzer for Signal Analysis, Certificate of Traceable Calibration Standard	70%
SDI7	Dual Channel SD/HD/3G-SDI Test Signal Generator Module for TG8000 or TG700 mainframe (O	80%
SPG700	Multiformat Sync Reference Generator - loop through genlock, 3 analog black burst or HD tri-le	50%
SPG8000A	Master Sync / Master Clock Reference Generator base unit - loop through genlock, 3 analog bla	20%
TAP1500	Active Probe: 1.5 GHz, 10X, Single-ended, TekVPI	15%
TAP2500	Active Probe: 2.5 GHz, 10X, Single-ended, TekVPI	15%
TAP3500	Active Probe: 3.5 GHz, 10X, Single-ended, TekVPI	15%
TBS1052B	Digital Storage Oscilloscope: 50MHz bandwidth, 1GS/s sample rate, 2 channel, 2.5K record leng	20%
TBS1064	Digital Storage Oscilloscope: 60MHz bandwidth, 1GS/s sample rate, 4 channel, 2.5K record leng	20%
TBS1072B-EDU	Digital Storage Oscilloscope: 70MHz bandwidth, 1GS/s sample rate, 2 channel, 2.5K record leng	20%
TBS2074	Digital Storage Oscilloscope: 70MHz bandwidth, 1GS/s sample rate, 4 channel, 20M record leng	10%
TBX3000A	TekSmartLabTM hardware, to enable the instruments without LAN port to connect to network	20%
TCA-1MEG	AMPLIFIER; HIGH IMPEDANCE BUFFER;1 MEG OHM/10PF;TEKPROBE BNC-TO-TEKCONNECT;WI	15%
TCA-VPI50	TekVPI to TekConnect Adapter for 50ohm terminated accessories	15%
TCP0020	Probe, AC/DC Current; 20 Amp; 50 MHz BW; TekVPI Interface; Certificate of Traceable Calibrat	15%
TCP0030A	Probe, AC/DC Current; 30 Amp DC, DC TO 120 MHZ; with TekVPI Interface; Certificate of Tracea	15%
TCS70902	Tektronix Differential Calibration Source	15%
TDP0500	Differential Probe: 500 MHz, 5X/50X, +/- 42V, TekVPI	15%
TDP1000	Differential Probe: 1 GHz, 5X/50X, +/- 42V, TekVPI	15%
TDP3500	Differential Probe: 3.5 GHz, 5X, +/- 2V, TekVPI	15%
TDS2012C	Oscilloscope; Digital Storage, 100MHz, 2GS/s, 2-CH, TFT Color Display, USB Ports certificate of	20%
TDS3ION	Battery Charger for TDS3K, SAFETY CONTROLLED	15%
TDS3LIM	Application Module: Limit Testing	15%
TDS3TMT	Application Module: Telecom Mask Testing	15%
TEK-DPG	Accessory, Deskew Pulse Generator Signal Source with TekVPI Scope Interface	15%
TEK-USB-488	USB TO IEEE488 (GPIB) COMMUNICATIONS ADAPTOR FOR USBTMC-USB488 COMPLIANT TEKTRONIX	15%
TG700	VIDEO GENERATOR; MAINFRAME,MULTIFORMAT--CERTIFICATE OF TRACEABLE CALIBRATION S	50%
TG8000	Multi format Test Signal Generator Mainframe	50%
THP0301-B	300 MHz 10X passive probe blue	15%
THP0301-G	300 MHz 10X passive probe green	15%
THP0301-M	300 MHz 10X passive probe magenta	15%

THS3014	THS3000 Series Handheld Oscilloscope: 100MHz, 4 Channel	20%
THS3014-TK	THS3000 Series Handheld Oscilloscope with travel kit: 100MHz, 4 Channel	20%
THS3024-TK	THS3000 Series Handheld Oscilloscope with travel kit: 200MHz, 4 Channel	20%
TL725	2X4 Wire Ohm Tweezer Test Leads	15%
TLA6404	136 Channel, 25 GHz MagniVu Timing, 333 MHz State Clock, 2 Mb Record Length Logic Analyzer	15%
TLA7012	LOGIC ANALYZER, PORTABLE MAINFRAME, 2 MODULES, CERTIFICATE OF TRACEABLE CALIBRATION	40%
TLA7016	LOGIC ANALYZER, BENCHTOP MAINFRAME, 6 MODULES, CERTIFICATE OF TRACEABLE CALIBRATION	15%
TLA7BB4	TLA7000 LOGIC ANALYZER MODULE, 136 CHANNELS, 50 GHZ MAGNIVU TIMING, 750 MHZ STATE CLOCK	15%
TLA7SA16	TLA7000 Logic Analyzer Module; 16 Differential Inputs, x8, 8 GTs Serial, 8 GB Memory	15%
TMDP0200	Differential PROBE; 200 MHZ TekVPI DIFFERENTIAL MEDIUM VOLTAGE PROBE;TMPD0200	15%
TPA-N-PRE	External Preamp., TPA Connector, SMA input	15%
TPA-N-VPI	Probe adapter from Type-N connector to TekVPI	15%
TPP0101	Passive Probe: 100 MHz, 10X, BNC	15%
TPP0101-PK10	10-Pack of TPP0101 10X 100 MHZ PASSIVE VOLTAGE PROBES; COVERED BNC	15%
TPP0250	Passive Probe: 250 MHz, 10X, TekVPI	15%
TPP0500	Passive Probe: 500 MHz, 10X, TekVPI	35%
TPP1000	Passive Probe: 1 GHz, 10X, TekVPI	15%
TPSCHG	Battery Charger for TPS Series Oscilloscopes	15%
TRCP0300	Current Probe: 30 MHz, 250 mA to 300 A, AC-Only, BNC Interface	15%
TRCP0600	Current Probe: 30 MHz, 500 mA to 600 A, AC-Only, BNC Interface	15%
TSG4102A	Analog RF SG with 2 GHz Frequency coverage	30%
TSG4104A	Analog RF SG with 4 GHz Frequency coverage	30%
VNM-EDGE2	Sentry Edge Digital Content Monitor	60%
VNM-SASI	Sentry Content ASI Stream Monitor	60%
VNM-SEN	Sentry Video Quality Monitor, includes QoE, Chassis Only	40%
VNM-SGE	Sentry Digital Content Monitor, includes QoE monitoring module; IP multicast input	60%
VNM-SMX	Sentry Multiplex (Dual Interface) Chassis, motherboard GbE interface plus 2nd interface on optional	45%
WFM2200A	Portable 3G/HD/SD-SDI Waveform Monitor/Generator, with Li-Ion Battery (Option 3G required)	20%
WFM2300	Portable 3G/HD/SD-SDI Waveform Monitor/Generator, with Eye/Jitter measurement, Li-Ion Battery	20%
WFM50F01	PORTABLE HARD CARRYING CASE FOR WFM5000 OR WFM4000	20%
WFM50F06	FINAL ASSY; FILLER PANEL; COVERS UNUSED RACK, IDENTICAL TO THE 9 DIGIT 65049790X USED	40%
WFM5200	3G/HD/SD Waveform Monitor, 4 SDI Inputs (3G, HD and SD-SDI support on the same inputs-auto de	20%
WFM5250	3G/HD/SD Waveform Monitor, 2 SDI Inputs and 2 HDMI Inputs (Option 3G required for 3G-SDI)	20%
WFM6120	ADVANCED WAVEFORM MONITOR BASE UNIT, SD STANDARD, CERTIFICATE OF TRACEABLE CALIBRATION	80%
WFM8200	Advanced 3G/HD/SD Waveform Monitor, 2 SDI Inputs (3G-SDI, HD-SDI and SD-SDI support on t	40%
WFM8300	Adv. 3G/HD/SD Waveform Monitor and Analyzer, 2 SDI Inputs (3G/HD/SD same inputs-auto de	40%
WFMRACK-NN	19 inch, 3RU, full-depth, Dual Rack Cabinet that accommodates a combination of one or two W	40%
WVR4000	SD-SDI WAVEFORM RASTERIZER WITH TWO PASSIVE LOOPTHROUGH VIDEO INPUTS, ONE AES/	20%
WVR8300	Adv. 3G/HD/SD Waveform Rasterizer and Analyzer, 2 SDI Inputs (3G/HD/SD same inputs-auto c	40%
WVR8RFP	Remote Front Panel for WVR8xxx Series Waveform Rasterizer (includes 25 foot cable)	80%
WVRRFP	RASTERIZER REMOTE FRONT PANEL (INCLUDES 25 FOOT CABLE)-STATEMENT OF COMPLIANCE	50%